



Cisco 644-906

Implementing and Maintaining Cisco Technologies Using IOS XR - (IMTXR)

Thank You for Downloading 644-906 Updated Exam Questions

<https://certs4sale.com/cisco/644-906-pdf-exam-dumps>

Question: 1

Refer to the show environmental power-supply command output exhibit.

```
R/S/I  Modules          Capacity      Status
      (W)
0/PM0/*
  host    PM          3000          Ok
0/PM1/*
  host    PM          3000          Ok
0/PM2/*
  host    PM           0          Unpowered

R/S/I  Power Draw      Voltage      Current
      (W)          (V)          (A)
0/PM0/* 270.5          54.1          5.0
0/PM1/* 392.5          54.5          7.2
0/PM2/*  0.0           0.0          0.0
-----
Total: 663.0

Power Budget Summary for Rack 0
-----

Power Shelves Type: AC
Total Power Capacity:      6000W
Usable Power Capacity:     6000W
Supply Failure Protected Capacity: 3000W
Worst Case Power Used:     1850W

Slot                               Max Watts
-----
0/RSP0/CPU0                        235
0/RSP1/CPU0                       235(default)
0/2/CPU0                           630
0/ET0/SP                           375
0/ET1/SP                           375

Worst Case Power Available:  4150W
Supply Protected Capacity Available: 1150W
```

How much power is the system currently using?

A. 663 W

- B. 1150 W
- C. 1850 W
- D. 6000 W

Answer: A

Question: 2

Refer to the show environmental power-supply command output exhibit.

R/S/I	Modules	Capacity (W)	Status
0/PM0/*	host PM	3000	Ok
0/PM1/*	host PM	3000	Ok
0/PM2/*	host PM	0	Unpowered
R/S/I	Power Draw (W)	Voltage (V)	Current (A)
0/PM0/*	270.5	54.1	5.0
0/PM1/*	392.5	54.5	7.2
0/PM2/*	0.0	0.0	0.0

Total: 663.0			
Power Budget Summary for Rack 0			

Power Shelves Type: AC			
Total Power Capacity:		6000W	
Usable Power Capacity:		6000W	
Supply Failure Protected Capacity:		3000W	
Worst Case Power Used:		1850W	
Slot		Max Watts	
----		-----	
0/RSP0/CPU0		235	
0/RSP1/CPU0		235(default)	
0/2/CPU0		630	
0/FT0/SP		375	
0/FT1/SP		375	
Worst Case Power Available:		4150W	
Supply Protected Capacity Available:		1150W	

How many additional line cards of the same type that are currently in the system can you safely install and remain redundant in the worse power usage if there is a power supply failure?

- A. 1
- B. 2
- C. 3
- D. 4
- E. 5

Answer: A

Question: 3

What is the maximum long-term normal operating temperature of the Cisco CRS-1, ASR 9000 Series Routers, and XR 12000 Series Routers?

- A. 40C (104F)
- B. 50C (122F)
- C. 55C (131F)
- D. 65C (149F)

Answer: A

Question: 4

The Cisco CRS 16-Slot Line Card Chassis Site Planning Guide suggests having 48 inches of clearance behind the chassis. What would definitely happen to the system if there were only 28 inches of clearance behind the Cisco CRS 16-Slot Line Card Chassis?

- A. The system would overheat due to inadequate airflow.
- B. The fabric card could not be exchanged if one failed.
- C. The modular services card (MSC) could not be exchanged if one failed.
- D. The fan tray could not be exchanged if one failed.

Answer: D

Question: 5

How many planes are there in the Cisco CRS-3 switch fabric?

- A. 1
- B. 3
- C. 7
- D. 8

Answer: D

Question: 6

What is the cell size of the cells that traverse the switch fabric on the Cisco CRS-3?

- A. 128 bytes
- B. 136 bytes
- C. 144 bytes

- D. 200 bytes
- E. 288 bytes

Answer: B

Question: 7

Where are client interfaces terminated on the Cisco CRS-3?

- A. the modular services card
- B. the physical layer interface module(s)
- C. the switch fabric interface terminator
- D. the Service Processor 40
- E. the Service Processor 140

Answer: B

THANK YOU FOR DOWNLOADING 644-906 UPDATED EXAM QUESTIONS

Note: Thanks For Trying The Demo Of Our 644-906 Exam Product

Visit Our Site to Purchase the Full Set of Actual 644-906 Exam Questions With Answers.

Money Back Guarantee



Click The Link Below

<https://certs4sale.com/cisco/644-906-pdf-exam-dumps>