



CCIE 350-018

CCIE Security written (Version 4.1)

Thank You for Downloading 350-018 Updated Exam Questions

<https://certs4sale.com/cisco/350-018-pdf-exam-dumps>

Version: 39.1

Question: 1

Which two statements about Network Edge Authentication Technology (NEAT) are true? (Choose two.)


- A. It can be configured on both access ports and trunk ports.
- B. It allows you to configure redundant links between authenticator and supplicant switches
- C. It can be configured on both access ports and EtherChannel ports.
- D. It supports port-based authentication on the authenticator switch.
- E. It conflicts with auto-configuration
- F. It requires a standard ACL on the switch port.

Answer: AD


Question: 2

DRAG DROP

Drag and drop the components of a Teredo IPv6 packet from the left to the correct position in the packet on the right



Answer:



Question: 3

Which option describes the purpose of the RADIUS VAP-ID attribute?


- A. It sets the minimum bandwidth for the connection.
- B. It identifies the VLAN interface to which the client will be associated.
- C. It specifies the WLAN ID of the wireless LAN to which the client belongs.
- D. It sets the maximum bandwidth for the connection.
- E. It specifies the ACL ID to be matches against the client.
- F. It specifies the priority of the client.

Answer: C


Question: 4

DRAG DROP

Drag each attack type on the left to the matching attack category on the right.



Answer:



Question: 5

Which of the following Cisco IPS signature engine has relatively high memory usage?

- A. The STRING-TCP engine
- B. The NORMALIZER engine
- C. The STRING-UDP engine
- D. The STRING-ICMP engine

Answer: B

Question: 6

ASA v9.2 new feature

- A. not possible to point to null0
- B. support for policy based routing with route-map
- C. backup ASA does ospf neighbor

Answer: A

Question: 7

When you configure ip-port-map http port 8080. What would be the output?

A)

```
R1#sh ip port-map | i http
Default mapping: http      tcp port 80      system defined
Default mapping: http      tcp port 8080    user defined
Default mapping: https     tcp port 443     system defined
R1#
```

B)

```
R1#sh ip port-map | i http
Default mapping: http      tcp port 80      system defined
Default mapping: http      tcp port 8080    user defined
Default mapping: http      tcp port 8081    user defined
Default mapping: https     tcp port 443     system defined
R1#
```

C)

```
R1#sh ip port-map | i http
Default mapping: http      tcp port 80      system defined
Default mapping: http      tcp port 8080    user defined
Default mapping: http      tcp port 8081    user defined
Default mapping: http      tcp port 8008    user defined
Default mapping: https     tcp port 443     system defined
R1#
```

- A. Exhibit A
- B. Exhibit B
- C. Exhibit C

Answer: A

Question: 8

OSPFv3 mechanism of authentication? (choose two)

- A. AH
- B. ESP
- C. MD5
- D. SHA
- E. IP
- F. GRE

Answer: CD

Question: 9

WPA 2 with CCMP encryption? (choose three)

- A. AES Counter Mode is a block cipher that encrypts 128-bit blocks of data at a time with a 128-bit encryption key
- B. AES Counter Mode is a block cipher that encrypts 256-bit blocks of data at a time with a 256-bit encryption key
- C. it encrypt all traffic from the AP to the host
- D. The CCMP algorithm produces a message integrity code (MIC) that provides data origin authentication and data integrity for the wireless frame.
- E. CCMP is also referred to as CBC-IN-MAC.

Answer: ACD

Question: 10

same security level interface inter-traffic communication.

- A. asa support 101 security level and more than 101 interface (include sub-interface)
- B. ASA can assign different interface to the same security level
- C. by default, same security level port inter-traffic is not allowed
- D. ASA should activate inter-interface communication by default

Answer: ABC

Question: 11

DRAG DROP

Drag the employee designation to right on role they play.

employee designation

change initiator
operations manager
change manager
CAB

role they play

approve change request
submit RFC
change review & auditing compling change metrics
implement change

Answer:

employee designation

role they play

CAB
change initiator
change manager
operations manager

There are four major roles involved with the change management process, each with separate and distinct responsibilities. In the order of their involvement in a normal change, the roles are:

- Change initiator: The change initiator is the person who initially perceives the need for the change and develops, plans, and executes the steps necessary to meet the initial requirements for a Request for Change (RFC). like product manager, network architect, network engineer, service manager, security manager or support tier 1,2,3
- Change manager: Larger organizations require a dedicated change manager who is responsible for all changes
 - Updating and communicating change procedures
 - Leading a team to review and accept completed change requests with a focus on higher-risk changes
 - Managing and conducting periodic change review meetings
 - Compiling and archiving change requests
 - Auditing network changes to ensure that:
 - Change was recorded correctly with work matching the RFC
 - Change had appropriate risk level

- Configuration items were updated appropriately
- Documentation was updated appropriately
 - Change communication and notification
 - Managing change postmortems
 - Creating and compiling change management metrics
 - Change advisory board: The change advisory board (CAB) is a body that exists to support the authorization of changes and to assist change management in the assessment and prioritization of changes. When a CAB is convened, members should be chosen who are capable of ensuring that all changes within the scope of the CAB are adequately assessed from both a business and a technical viewpoint.

The CAB may be asked to consider and recommend the adoption or rejection of changes appropriate for higher-level authorization and then recommendations will be submitted to the appropriate change authority.

Potential members include:

Customers

User managers

User group representatives

Applications developers/maintainers

Specialists/technical consultants

Services and operations staff, such as service desk, test management, continuity management, security, and capacity

Facilities/office services staff (where changes may affect moves/accommodation and vice versa)

Contractors' or third parties' representatives, in outsourcing situations, for example

Other parties as applicable to specific circumstances (such as marketing if public products are affected).


- Change implementation team (operations)

http://www.cisco.com/c/en/us/products/collateral/services/high-availability/white_paper_c11-458050.html



Question: 12

DRAG DROP

Drag from left to right on correct action.



Answer:



Question: 13

Two routers are trying to establish an OSPFv3 adjacency over an Ethernet link, but the adjacency is not forming. Which two options are possible reasons that prevent OSPFv3 to form between these two routers? (Choose two.)

- A. mismatch area types
- B. mismatch of subnet masks
- C. mismatch of network types
- D. mismatch of authentication types
- E. mismatch of instance IDs

Answer: AE

Question: 14


The computer at 10.10.10.4 on your network has been infected by a botnet that directs traffic to a malware site at 168.65.201.120. Assuming that filtering will be performed on a Cisco ASA, what command can you use to block all current and future connections from the infected host?

- A. ip access-list extended BLOCK_BOT_OUT deny ip any host 10.10.10.4
- B. shun 168.65.201.120 10.10.10.4 6000 80
- C. ip access-list extended BLOCK_BOT_OUT deny ip host 10.10.10.4 host 168.65.201.120
- D. shun 10.10.10.4 168.65.201.120 6000 80

Answer: B

Question: 15

Refer to the exhibit.



```
RTP-A(config-if)# ip tcp adjust-mss 1452
RTP-A(config-if)# ip mtu 1492
```


Which effect of this configuration is true?

- A. The MSS of TCP SYN packets is set to 1452 bytes and the IP MTU of the interface is set to 1492 bytes
- B. The maximum size of TCP SYN+ACK packets passing the transient host is set to 1452 bytes and the IP MTU of the interface is set to 1492 bytes
- C. The PMTUD values sets itself to 1452 bytes when the interface MTU is set to 1492 bytes
- D. SYN packets carries 1452 bytes in the payload when the Ethernet MTU of the interface is to 1492 bytes
- E. The maximum size of TCP SYN+ACK packets passing the router is set to 452 bytes and the IP MTU of the interface is set to 1492 bytes

Answer: A

Question: 16

Refer to the exhibit.



```
RTP-A(config-if)# ipv6 mld report-link-local-groups
```

Which effect of this configuration is true?

- A. It configures the node to generate a link-local group report when it joins the solicited-node multicast group
- B. It enables local group membership for MLDv1 and MLDv2
- C. It enables hosts to send MLD report messages for groups in 224.0.0.0/24
- D. It enables MLD query messages for all link-local groups
- E. It enables the host to send MLD report messages for nonlink local groups

Answer: C

Question: 17

You have configured an ASA firewall in multiple context mode. If the context are sharing an Interface. What are two of the actions you could take to classify packets to the appropriate


Context?(Choose two)

- A. Enable DHCP
- B. Disable MAC auto-generation and adding unique IP addresses to each interface
- C. Enable MAC auto-generation globally
- D. Assign a unique MAC address to each interface
- E. Apply QoS to each interface

Answer: CD

Question: 18

Refer to the exhibit.



```
aaa-server adm_net protocol radius
aaa-server adm_net (inside) host 10.20.10.10
aaa authentication enable console adm_net
aaa authentication ssh console adm_net
aaa authorization exec authentication-server
```

What is the effect of the given configuration?

- A. It requires the enable password to be authorized by the LOCAL database
- B. It allows users to log in with any user name in the LOCAL database
- C. It enables management authorization for a user-authenticated RADIUS server
- D. Users will be authenticated against the RADIUS servers defined in the adm_net list
- E. It allows SSH connections to console login into the ASA

Answer: D

Question: 19

What feature enables extended secure access from non-secure physical locations?

- A. NEAT
- B. 802.1X port-based authentication
- C. port security
- D. storm-control
- E. CBAC

Answer: A

Question: 20

What are the two technologies that support AFT?(Choose two)

- A.NAT-6to 4
- B.NAT-PT
- C.DNAT
- D.NAT64
- E.NAT-PMP
- F.SNAT

Answer: BD

THANK YOU FOR DOWNLOADING 350-018 UPDATED EXAM QUESTIONS

Note: Thanks For Trying The Demo Of Our 350-018 Exam Product

Visit Our Site to Purchase the Full Set of Actual 350-018 Exam Questions With Answers.

Money Back Guarantee



Click The Link Below

<https://certs4sale.com/cisco/350-018-pdf-exam-dumps>